

Package: ontoProc (via r-universe)

May 29, 2026

Title processing of ontologies of anatomy, cell lines, and so on

Description Support harvesting of diverse bioinformatic ontologies, making particular use of the ontologyIndex package on CRAN. We provide snapshots of key ontologies for terms about cells, cell lines, chemical compounds, and anatomy, to help analyze genome-scale experiments, particularly cell x compound screens. Another purpose is to strengthen development of compelling use cases for richer interfaces to emerging ontologies.

Version 2.7.0

Imports Biobase, S4Vectors, methods, stats, utils, BiocFileCache, shiny, graph, Rgraphviz, ontologyPlot, dplyr, magrittr, DT, igraph, AnnotationHub, SummarizedExperiment, reticulate, R.utils, httr, basilisk, jsonlite, RBGL, ellmer

Suggests knitr, org.Hs.eg.db, org.Mm.eg.db, testthat, BiocStyle, SingleCellExperiment, celldex, rmarkdown, AnnotationDbi, magick,

Depends R (>= 4.1), ontologyIndex

License Artistic-2.0

LazyLoad yes

biocViews Infrastructure, GO

RoxygenNote 7.3.2

VignetteBuilder knitr

Encoding UTF-8

Collate 'CLextend.R' 'CLfeats.R' 'autism_details.R'
'available_ontos.R' 'basilisk.R' 'bind_formal_tags.R'
'bioregistry.R' 'clfixer.R' 'common_classes.R'
'connect_classes.R' 'countClasses.R' 'ctmarks.R' 'data.R'
'dropStop.R' 'fastGrep.R' 'findCommonAncestors.R' 'formalize.R'
'getOntos.R' 'get_ordo_owl_path.R' 'graphNEL.R' 'mapNaive.R'
'nio_details.R' 'ontoDiff.R' 'owl2cache.R' 'owl_ops.R'
'plot.owlents.R' 'quickOnto.R' 'roots.R' 'setup_entities2.R'
'seurTab.R' 'shiny.R' 'subset_descendants.R' 'sym2CellOnto.R'
'termProc.R' 'treeproc.R'

URL <https://github.com/vjcitn/ontoProc>

BugReports <https://github.com/vjcitn/ontoProc/issues>

Config/pak/sysreqs cmake libglpk-dev make libicu-dev libpng-dev libuv1-dev libxml2-dev libssl-dev python3 zlib1g-dev

Repository <https://tempbioc.r-universe.dev>

Date/Publication 2026-04-28 18:29:37 UTC

RemoteUrl <https://github.com/bioc/ontoProc>

RemoteRef HEAD

RemoteSha 9f24f7924ba42392967929c5117c531b67c4fe4c

Contents

| | |
|-------------------------------------|----|
| [.owlents | 3 |
| allGOterms | 4 |
| ancestors | 5 |
| ancestors_names | 5 |
| available_ontos | 6 |
| bind_formal_tags | 6 |
| bioregistry_ols_resources | 7 |
| browse_ontos | 8 |
| c,TermSet-method | 8 |
| cellTypeToGO | 9 |
| children_names | 10 |
| cleanCLOnames | 10 |
| CLfeats | 11 |
| common_classes | 12 |
| connect_classes | 12 |
| ctmarks | 13 |
| cyclicSigset | 14 |
| demoApp | 15 |
| dropStop | 15 |
| fastGrep | 16 |
| findCommonAncestors | 17 |
| formalize | 18 |
| get_classes | 19 |
| get_ordo_owl_path | 20 |
| getChebiLite | 20 |
| getLeavesFromTerm | 21 |
| getOnto | 22 |
| graph2paths | 22 |
| humrna | 23 |
| improveNodes | 24 |
| jowl2classgraph | 24 |
| jowl2classgraph_nio | 25 |
| labels.owlents | 25 |

| | |
|--|----|
| ldfToTerms | 26 |
| liberalMap | 27 |
| make_graphNEL_from_ontology_plot | 28 |
| makeSelectInput | 29 |
| map2prose | 30 |
| mapOneNaive | 30 |
| minicorpus | 31 |
| nomenCheckup | 31 |
| onto_plot2 | 32 |
| onto_roots | 33 |
| ontoDiff | 33 |
| owl2cache | 34 |
| packDesc2019 | 35 |
| packDesc2021 | 35 |
| packDesc2022 | 36 |
| packDesc2023 | 36 |
| parents | 37 |
| plot.owlents | 37 |
| print.owlents | 38 |
| PROSYM | 39 |
| quickOnto | 39 |
| recognizedPredicates | 40 |
| search_labels | 40 |
| secLevGen | 41 |
| selectFromMap | 42 |
| setup_entities | 42 |
| setup_entities2 | 43 |
| seur3kTab | 44 |
| siblings_TAG | 44 |
| stopWords | 45 |
| subclasses | 46 |
| subset_descendants | 46 |
| sym2CellOnto | 47 |
| TermSet-class | 48 |
| url_ok | 48 |
| valid_ontonyms | 49 |

Index **50**

[.owlents *subset method*

Description

subset method

Usage

```
## S3 method for class 'owlents'  
x[i, j, drop = FALSE]
```

Arguments

| | |
|------|-----------------------------|
| x | owlents instance |
| i | character or numeric vector |
| j | not used |
| drop | not used |

| | |
|------------|--|
| allGOterms | <i>allGOterms: data.frame with ids and terms</i> |
|------------|--|

Description

allGOterms: data.frame with ids and terms

Usage

```
allGOterms
```

Format

data.frame instance

Source

This is a snapshot of all the terms available from GO.db (3.4.2), August 2017, using `keys(GO.db, keytype="TERM")`.

Examples

```
data(allGOterms)  
head(allGOterms)
```

| | |
|-----------|---------------------------------|
| ancestors | <i>retrieve ancestor 'sets'</i> |
|-----------|---------------------------------|

Description

retrieve ancestor 'sets'

Usage

```
ancestors(oe)
```

Arguments

oe owlents instance

Value

a list of sets

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  orde
  ancestors(orde[1:5])
  labels(orde[1:5])
}
```

| | |
|-----------------|---|
| ancestors_names | <i>obtain list of names of a set of ancestors</i> |
|-----------------|---|

Description

obtain list of names of a set of ancestors

Usage

```
ancestors_names(anclist)
```

Arguments

anclist output of 'ancestors'

Value

list of vectors of character()

Note

non-entities are removed and names are extracted

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  al = ancestors(orde[1001:1002])
  ancestors_names(al)
}
```

| | |
|-----------------|---|
| available_ontos | <i>interrogate the cache for owl files and serialized ontologyIndex instances</i> |
|-----------------|---|

Description

interrogate the cache for owl files and serialized ontologyIndex instances

Usage

```
available_ontos(ca = BiocFileCache::BiocFileCache(), token = "owl|OIRDS")
```

Arguments

| | |
|-------|--|
| ca | defaults to BiocFileCache::BiocFileCache() |
| token | character(1) defaults to "owl OIRDS" |

Value

NULL if nothing relevant is found in cache, otherwise a data.frame with all cached information

| | |
|------------------|---|
| bind_formal_tags | <i>add mapping from informal to formal cell type tags to a SummarizedExperiment colData</i> |
|------------------|---|

Description

add mapping from informal to formal cell type tags to a SummarizedExperiment colData

Usage

```
bind_formal_tags(se, informal, tagmap, force = FALSE)
```

Arguments

| | |
|----------|--|
| se | SummarizedExperiment instance |
| informal | character(1) name of colData element with uncontrolled vocabulary |
| tagmap | data.frame with columns 'informal' and 'formal' |
| force | logical(1), defaults to FALSE; if TRUE, allows clobbering existing colData variable named "formal" |

Value

SummarizedExperiment instance with a new colData column 'label.ont' giving the formal tags associated with each sample

Note

This function will fail if the value of 'informal' is not among the colData variable names, or if "formal" is among the colData variable names.

bioregistry_ols_resources
produce bioregistry_ols table

Description

produce bioregistry_ols table

Usage

```
bioregistry_ols_resources()
```

Value

data.frame

Note

This uses the 'resources' method of the bioregistry module from pip to isolate resources with a non-null 'ols' component.

Examples

```
tab = bioregistry_ols_resources()  
head(tab[,1:3])
```

| | |
|--------------|---|
| browse_ontos | <i>browse available ontologies with datatable</i> |
|--------------|---|

Description

browse available ontologies with datatable

Usage

```
browse_ontos(ca = BiocFileCache::BiocFileCache(), token = "owl|OIRDS")
```

Arguments

| | |
|-------|--|
| ca | defaults to BiocFileCache::BiocFileCache() |
| token | character(1) defaults to "owl OIRDS" |

| | |
|-------------------|----------------------------------|
| c, TermSet-method | <i>combine TermSet instances</i> |
|-------------------|----------------------------------|

Description

combine TermSet instances

Usage

```
## S4 method for signature 'TermSet'
c(x, ...)
```

Arguments

| | |
|-----|----------------------|
| x | TermSet instance |
| ... | additional instances |

Value

TermSet instance

| | |
|--------------|---|
| cellTypeToGO | <i>utilities for approximate matching of cell type terms to GO categories and annotations</i> |
|--------------|---|

Description

utilities for approximate matching of cell type terms to GO categories and annotations

Usage

```
cellTypeToGO(celltypeString, gotab, ...)
```

```
cellTypeToGenes(  
  celltypeString,  
  gotab,  
  orgDb,  
  cols = c("ENSEMBL", "SYMBOL"),  
  ...  
)
```

Arguments

| | |
|----------------|--|
| celltypeString | character atom to be used to search GO terms using |
| gotab | a data.frame with columns GO (goids) and TERM (term strings) agrep |
| ... | additional arguments to agrep |
| orgDb | instances of orgDb |
| cols | columns to be retrieved in select operation |

Value

data.frame
data.frame

Note

Very primitive, uses [agrep](#) to try to find relevant terms.

Examples

```
library(org.Hs.eg.db)  
data(allGOterms)  
head(cellTypeToGO("serotonergic neuron", allGOterms))  
head(cellTypeToGenes("serotonergic neuron", allGOterms, org.Hs.eg.db))
```

| | |
|----------------|---|
| children_names | <i>obtain list of names of a set of subclasses/children</i> |
|----------------|---|

Description

obtain list of names of a set of subclasses/children

Usage

```
children_names(sclist)
```

Arguments

sclist output of 'subclasses'

Value

list of vectors of character()

Note

non-entities are removed and names are extracted

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  al = subclasses(orde[100:120])
  children_names(al)
}
```

| | |
|--------------|--|
| cleanCLNames | <i>obtain named character vector of terms from Cell Line Ontology, omitting obsolete and trailing 'cell'</i> |
|--------------|--|

Description

obtain named character vector of terms from Cell Line Ontology, omitting obsolete and trailing 'cell'

Usage

```
cleanCLNames()
```

Value

character()

Examples

```
cleanCLNames()[1:10]
```

CLfeats

produce a data.frame of features relevant to a Cell Ontology class

Description

produce a data.frame of features relevant to a Cell Ontology class

Usage

```
CLfeats(ont, tag = "CL:0001054", pr, go)
```

Arguments

| | |
|-----|--|
| ont | instance of ontologyIndex ontology |
| tag | character(1) a CL: class tag |
| pr | instance of ontologyIndex PRO protein ontology |
| go | instance of ontologyIndex GO gene ontology |

Value

a data.frame instance

Note

This function will look in the intersection_of and has_part, lacks_part components of the CL entry to find properties asserted of or inherited by the cell type identified in 'tag'. As of 1.19, this function does not look in global environment for ontologies. We use 2021 versions in the examples because some changes in ontologies omit important relationships; revisions to package code after 1.19.4 will attempt to address these.

Examples

```
c1 = getOnto("cellOnto", year_added="2021")
pr = getOnto("Pronto", "2021") # legacy tag, for 2022 would be PROnto
go = getOnto("goOnto", "2021")
CLfeats(c1, tag="CL:0001054", pr=pr, go=go)
```

| | |
|----------------|---|
| common_classes | <i>list and count samples with common ontological annotation in two SEs</i> |
|----------------|---|

Description

list and count samples with common ontological annotation in two SEs

Usage

```
common_classes(ont, se1, se2)
```

Arguments

| | |
|-----|--|
| ont | instance of ontologyIndex ontology |
| se1 | a SummarizedExperiment using 'label.ont' in colData to provide ontological tags (from 'ont') for samples |
| se2 | a SummarizedExperiment using 'label.ont' in colData to provide ontological tags (from 'ont') for samples |

Value

a data.frame with rownames given by the common tags, the class names as column 'cname', and counts of samples bearing the given tags in remaining columns.

Examples

```
if (requireNamespace("celldex")) {
  imm = celldex::ImmGenData()
  if ("label.ont" %in% names(SummarizedExperiment::colData(imm))) {
    cl = getOnto("cellOnto")
    blu = celldex::BlueprintEncodeData()
    common_classes( cl, imm, blu )
  }
}
```

| | |
|-----------------|--|
| connect_classes | <i>connect ontological categories between related, annotated SummarizedExperiments</i> |
|-----------------|--|

Description

connect ontological categories between related, annotated SummarizedExperiments

Usage

```
connect_classes(ont, se1, se2)
```

Arguments

| | |
|-----|--|
| ont | an ontologyIndex ontology instance |
| se1 | SummarizedExperiment instance with 'label.ont' among colData columns |
| se2 | SummarizedExperiment instance with 'label.ont' among colData columns |

Value

a list with two sublists mapping from terms in one SE to descendant terms in the other SE

| | |
|---------|---|
| ctmarks | <i>app to review molecular properties of cell types via cell ontology</i> |
|---------|---|

Description

app to review molecular properties of cell types via cell ontology

Usage

```
ctmarks(cl, pr, go)
```

Arguments

| | |
|----|---|
| cl | an import of a Cell Ontology (or extended Cell Ontology) in ontology_index form |
| pr | an import of a Protein Ontology in ontology_index form |
| go | an import of a Gene Ontology in ontology_index form |

Value

a data.frame with features for selected cell types

Note

Prototype of harvesting of cell ontology by searching has_part, has_plasma_membrane_part, intersection_of and allied ontology relationships. Uses shiny. Can perform better if getPROnto() and getGeneOnto() values are in .GlobalEnv as pr and go respectively.

Examples

```
if (interactive()) {
  co = getOnto("cellOnto", year_added="2023") # has plasma membrane relations
  go = getOnto("goOnto", "2023")
  pr = getOnto("Pronto", "2021") # peculiar tag used in legacy, would be PROnto with 2022
  ctmarks(co, go, pr)
}
```

| | |
|--------------|--|
| cyclicSigset | <i>as in Bakken et al. (2017 PMID 29322913) create gene signatures for k cell types, each of which fails to express all but one gene in a set of k genes</i> |
|--------------|--|

Description

as in Bakken et al. (2017 PMID 29322913) create gene signatures for k cell types, each of which fails to express all but one gene in a set of k genes

Usage

```
cyclicSigset(
  idvec,
  conds = c("hasExp", "lacksExp"),
  tags = paste0("CL:X", 1:length(idvec))
)
```

Arguments

| | |
|-------|---|
| idvec | character vector of identifiers, must have names() set to identify cells bearing genes |
| conds | character(2) tokens used to indicate condition to which signature element contributes |
| tags | character vector of cell-type identifiers; for Cell Ontology use CL: as prefix, one element for each element of idvec |

Value

a long data.frame

Examples

```
sigels = c("CL:X01"="GRIK3", "CL:X02"="NTNG1", "CL:X03"="BAGE2",
           "CL:X04"="MC4R", "CL:X05"="PAX6", "CL:X06"="TSPAN12", "CL:X07"="hSHISA8",
           "CL:X08"="SNGC", "CL:X09"="ARHGEF28", "CL:X10"="EGF")
sigdf = cyclicSigset(sigels)
head(sigdf)
```

| | |
|---------|---|
| demoApp | <i>demonstrate the use of makeSelectInput</i> |
|---------|---|

Description

demonstrate the use of makeSelectInput

Usage

```
demoApp()
```

Value

Run only for side effect of starting a shiny app.

Examples

```
if (interactive()) {  
  require(shiny)  
  print(demoApp())  
}
```

| | |
|----------|--|
| dropStop | <i>dropStop is a utility for removing certain words from text data</i> |
|----------|--|

Description

dropStop is a utility for removing certain words from text data

Usage

```
dropStop(x, drop, lower = TRUE, splitby = " ")
```

Arguments

| | |
|---------|--|
| x | character vector of strings to be cleaned |
| drop | character vector of words to scrub |
| lower | logical, if TRUE, x converted with tolower |
| splitby | character, used with strsplit to tokenize x |

Value

a list with one element per input string, split by " ", with elements in drop removed

Examples

```
data(minicorpus)
minicorpus[1:3]
dropStop(minicorpus)[1:3]
```

| | |
|----------|--|
| fastGrep | <i>some fields of interest are lists, and grep per se should not be used – this function checks and uses grep within vapply when appropriate</i> |
|----------|--|

Description

some fields of interest are lists, and grep per se should not be used – this function checks and uses grep within vapply when appropriate

Usage

```
fastGrep(patt, onto, field, ...)
```

Arguments

| | |
|-------|--|
| patt | a regular expression whose presence in field should be checked |
| onto | an ontologyIndex instance |
| field | the ontologyIndex component to be searched |
| ... | passed to grep |

Value

logical vector indicating vector or list elements where a match is found

Examples

```
cheb = getOnto("chebi_lite")
ind = fastGrep("tanespimycin", cheb, "name")
cheb$name[ind]
```

findCommonAncestors *Find common ancestors*

Description

Given a set of ontology terms, find their latest common ancestors based on the term hierarchy.

Usage

```
findCommonAncestors(..., g, remove.self = TRUE, descriptions = NULL)
```

Arguments

| | |
|--------------|--|
| ... | One or more (possibly named) character vectors containing ontology terms. |
| g | A graph object containing the hierarchy of all ontology terms. |
| remove.self | Logical scalar indicating whether to ignore ancestors containing only a single term (themselves). |
| descriptions | Named character vector containing plain-English descriptions for each term. Names should be the term identifier while the values are the descriptions. |

Details

This function identifies all terms in `g` that are the latest common ancestor (LCA) of any subset of terms in `...`. An LCA is one that has no children that have the exact same set of descendent terms in `...`, i.e., it is the most specific term for that set of observed descendents. Knowing the LCA is useful for deciding how terms should be rolled up to broader definitions in downstream applications, usually when the exact terms in `...` are too specific for practical use.

The descendents `DataFrame` in each row of the output describes the descendents for each LCA, stratified by their presence or absence in each entry of `...`. This is particularly useful for seeing how different sets of terms would be aggregated into broader terms, e.g., when harmonizing annotation from different datasets or studies. Note that any names for `...` will be reflected in the columns of the `DataFrame` for each LCA.

Value

A `DataFrame` where each row corresponds to a common ancestor term. This contains the columns number, the number of descendent terms across all vectors in `...`; and descendents, a [List](#) of `DataFrames` containing the identities of the descendents. It may also contain the column description, containing the description for each term.

Author(s)

Aaron Lun

Examples

```

co <- getOnto("cellOnto")

# TODO: wrap in utility function.
parents <- co$parents
self <- rep(names(parents), lengths(parents))
library(igraph)
g <- make_graph(rbind(unlist(parents), self))

# Selecting random terms:
LCA <- ontoProc::findCommonAncestors(A=sample(names(V(g)), 20),
  B=sample(names(V(g)), 20), g=g)

LCA[1,]
LCA[1,"descendents"][[1]]

```

formalize

use an LLM to match informal terms to terms in an ontology

Description

use an LLM to match informal terms to terms in an ontology

Usage

```

formalize(
  informal_terms,
  ontology_terms,
  ontology_tags,
  ellmer_chatfun = ellmer::chat_openai,
  llm_model = "gpt-4.1-2025-04-14"
)

```

Arguments

`informal_terms` `character()` vector of terms not necessarily found in ontology

`ontology_terms` `character()` vector of ontology terms

`ontology_tags` `character()` vector of tags for ontology terms, must be of same length as `ontology_terms`

`ellmer_chatfun` function available in `ellmer` to connect to chatbot

`llm_model` `character(1)` used with `chat_openai` in `ellmer`, defaults to "gpt-4.1-2025-04-14", or other models for other providers available through `ellmer`.

Value

A data.frame with columns `informal_term`, `formal_term`, `similarity_score`, and `tag`. Invisible attributes `chat_tokens`, `chat_cost`, and `chat_provider` are also present.

Note

Expects to have OPENAI_API_KEY set if an openai chatfun is used, or GOOGLE_API_KEY if, e.g., a gemini chatfun is used.

Examples

```
if (interactive()) {
  ctypes = c("tPlasma cells", "tMoMacDC", "tT cells", # from Zilionis
    "tB cells", "tNK cells", "tNeutrophils", "Fibroblasts", "Type II cells",
    "tpDC", "Endothelial cells", "tMast cells", "Smooth muscle cells",
    "ND", "Club cells", "bNeutrophils", "bT cells", "bMonocytes",
    "bNK cells", "bRBC", "bpDC", "bB cells", "bPlasma cells", "bPlatelets",
    "tRBC", "Type I cells", "Ciliated cells", "bBasophils")
  cc = owl2cache(url="http://purl.obolibrary.org/obo/cl.owl")
  cloi = setup_entities2(cc)
  oname = cloi$name
  actual = grep("CL_", names(oname))
  oterms = as.character(oname[actual])
  otags = names(oname[actual])
  octy = formalize(ctypes, oterms, otags)
  head(octy)
  attr(octy, "chat_tokens")
  onto_plot2(cloi, unique(na.omit(octy$tag)), cex=.55)
}
```

get_classes

return a generator with ontology classes

Description

return a generator with ontology classes

Usage

```
get_classes(owlfile)
```

Arguments

owlfile reference to OWL file, can be URL, will be processed by owlready2.get_ontology

Value

generator with output of classes() on the loaded ontology

| | |
|-------------------|---------------------------------|
| get_ordo_owl_path | <i>decompress ordo owl file</i> |
|-------------------|---------------------------------|

Description

decompress ordo owl file

Usage

```
get_ordo_owl_path(target = tempdir())
```

Arguments

| | |
|--------|---|
| target | character(1) path to where decompressed owl will live |
|--------|---|

| | |
|--------------|---|
| getChebiLite | <i>basic getters in old style, retained 2023 for deprecation interval</i> |
|--------------|---|

Description

basic getters in old style, retained 2023 for deprecation interval

Usage

```
getChebiLite()
```

```
getCellosaurusOnto()
```

```
getUBERON_NE()
```

```
getChebiOnto()
```

```
getOncotreeOnto()
```

```
getDiseaseOnto()
```

```
getGeneOnto()
```

```
getHCAOnto()
```

```
getPROnto()
```

```
getPATOnto()
```

```
getMondoOnto()
```

```
getSI00nto()
```

Value

instance of ontology_index (S3) from ontologyIndex

Note

getChebiOnto loads ontoRda/chebi_full.rda

getOncotreeOnto loads ontoRda/oncotree.rda

getDiseaseOnto loads ontoRda/diseaseOnto.rda

getHCAOnto loads ontoRda/hcaOnto.rda produced from hcao.owl at [https://github.com/HumanCellAtlas/ontology/releases/tag/2/11/2019](https://github.com/HumanCellAtlas/ontology/releases/tag/2019-02-11), python pronto was used to convert OWL to OBO.

getPROnto loads ontoRda/PROnto.rda, produced from <http://purl.obolibrary.org/obo/pr.obo> 'reasoned' ontology from OBO foundry, 02-08-2019. In contrast to other ontologies, this is imported via get_OBO with 'extract_tags='minimal' '.

getPATOnto loads ontoRda/patoOnto.rda, produced from <https://raw.githubusercontent.com/pato-ontology/pato/master/pato.obo> from OBO foundry, 02-08-2019.

| | |
|-------------------|---|
| getLeavesFromTerm | <i>obtain childless descendents of a term (including query)</i> |
|-------------------|---|

Description

obtain childless descendents of a term (including query)

Usage

```
getLeavesFromTerm(x, ont)
```

Arguments

| | |
|-----|--|
| x | a character(1) id element for ontology_index instance |
| ont | an ontology_index instance as defined in ontologyIndex package |

Value

character vector of 'leaves' of ontology tree

Examples

```
ch = getOnto("chebi_lite")
alldr = getLeavesFromTerm("CHEBI:23888", ch)
head(ch$name[alldr[1:15]])
```

| | |
|---------|---|
| getOnto | <i>get the ontology based on a short tag and year</i> |
|---------|---|

Description

get the ontology based on a short tag and year

Usage

```
getOnto(ontname = "cellOnto", year_added = "2023")
```

Arguments

| | |
|------------|---|
| ontname | character(1) must be an element in 'valid_ontnames()' |
| year_added | character(1) refers to 'rdatadateadded' in AnnotationHub metadata |

Note

This queries AnnotationHub for "ontoProcData" and then filters to find the AnnotationHub accession number and retrieves the ontologyIndex serialization of the associated OBO representation of the ontology.

Examples

```
co = getOnto()
tail(co$name[1000:1500])
```

| | |
|-------------|---|
| graph2paths | <i>produce list of vectors of (shortest) paths from root to all nodes in gr</i> |
|-------------|---|

Description

produce list of vectors of (shortest) paths from root to all nodes in gr

Usage

```
graph2paths(gr, root = "http://www.ifomis.org/bfo/1.1#Entity", excise = NULL)
```

Arguments

| | |
|--------|--|
| gr | graphNEL (package graph) instance representing an ontology |
| root | character(1) node from which to produce paths |
| excise | character() or NULL, path steps to exclude |

Examples

```
if (!requireNamespace("graph")) stop("install graph package from Bioconductor to use this function")
jpath = system.file("json", "aut.json.gz", package="ontoProc")
cg = jowl2classgraph(jpath,
  dropstrings = "http://purl.org/autism-ontology/1.0/autism-rules.owl#")
evec = grep("span\\#|snap\\#", graph::nodes(cg), value=TRUE)
paths = graph2paths(cg, excise=evec)
tail(paths)
```

humrna

humrna: a data.frame of SRA metadata related to RNA-seq in humans

Description

humrna: a data.frame of SRA metadata related to RNA-seq in humans

Usage

```
humrna
```

Format

```
data.frame
```

Note

arbitrarily chosen from RNA-seq studies for taxon 9606

Source

NCBI SRA

Examples

```
data(humrna)
names(humrna)
head(humrna[, 1:5])
```

| | |
|--------------|---|
| improveNodes | <i>inject linefeeds for node names for graph, with textual annotation from ontology</i> |
|--------------|---|

Description

inject linefeeds for node names for graph, with textual annotation from ontology

Usage

```
improveNodes(g, ont)
```

Arguments

| | |
|-----|---|
| g | graphNEL instance |
| ont | instance of ontology from ontologyIndex |

| | |
|-----------------|---|
| jowl2classgraph | <i>extract class relationship graph from JSON representation of OWL</i> |
|-----------------|---|

Description

extract class relationship graph from JSON representation of OWL

Usage

```
jowl2classgraph(
  jsonpath,
  dropstrings = c("http://www.ifomis.org/bfo/1.1/snap#",
                 "http://purl.org/autism-ontology/1.0/autism-rules.owl#")
)
```

Arguments

| | |
|-------------|---|
| jsonpath | character(1) path to JSON, typically generated by java robot applied to owl |
| dropstrings | character(), strings to be excised from class names |

Value

graphNEL with edgemode 'directed'

Examples

```
if (!requireNamespace("graph")) stop("install graph package from Bioconductor to use this function")
jpath = system.file("json", "aut.json.gz", package="ontoProc")
cg = jowl2classgraph(jpath,
  dropstrings = "http://purl.org/autism-ontology/1.0/autism-rules.owl#")
head(graph::nodes(cg))
```

| | |
|---------------------|---|
| jowl2classgraph_nio | <i>extract class relationship graph from JSON representation of OWL for NIO</i> |
|---------------------|---|

Description

extract class relationship graph from JSON representation of OWL for NIO

Usage

```
jowl2classgraph_nio(jsonpath, dropstrings = NULL)
```

Arguments

| | |
|-------------|---|
| jsonpath | character(1) path to JSON, typically generated by java robot applied to owl |
| dropstrings | character(), strings to be excised from class names |

Value

graphNEL with edgemode 'directed'

Examples

```
if (!requireNamespace("graph")) stop("install graph package from Bioconductor to use this function")
jpath = system.file("json", "nio.json.gz", package="ontoProc")
cg = jowl2classgraph_nio(jpath,
  dropstrings = "http://purl.org/autism-ontology/1.0/autism-rules.owl#")
head(graph::nodes(cg))
```

| | |
|----------------|-----------------------------------|
| labels.owlents | <i>retrieve labels with names</i> |
|----------------|-----------------------------------|

Description

retrieve labels with names

Usage

```
## S3 method for class 'owlents'
labels(object, ...)
```

Arguments

| | |
|--------|------------------|
| object | owlents instance |
| ... | not used |

Note

When multiple labels are present, only first is silently returned. Note that reticulate 1.35.0 made a change that appears to imply that '[0]' can be used to retrieve the desired components. To get ontology tags, use 'names(labels(...))'. Note: This function was revised Jul 12 2024 to allow terms that lack labels (like CHEBI references in cl.owl) to be processed, returning NA. The previous functionality which failed is available, not exported, as labelsOLD.owlents.

Examples

```
## Not run:
clont_path = owl2cache(url="http://purl.obolibrary.org/obo/cl.owl")
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  clont = setup_entities(clont_path)
  labels(clont[1:5])
  labels(clont[51:55])
}

## End(Not run) # dontrun introduced because of ambiguity in STATO term usage; see vignettes for repaired example
```

| | |
|------------|--|
| ldfToTerms | <i>use output of cyclicSigset to generate a series of character vectors constituting OBO terms</i> |
|------------|--|

Description

use output of cyclicSigset to generate a series of character vectors constituting OBO terms

Usage

```
ldfToTerms(
  ldf,
  propmap,
  sigels,
  prologMaker = function(id, ...) sprintf("id: %s", id)
)
```

Arguments

| | |
|-------------|---|
| ldf | a 'long format' data.frame as created by cyclicSigset |
| propmap | a character vector with names of elements corresponding to 'abbreviated' relationship tokens and element values corresponding to full relationship-naming strings |
| sigels | a named character vector associating cell types (names) to genes expressed in a cyclic set, one element per type |
| prologMaker | a function with arguments (id, ...), in which id is character(1), that generates a vector of strings that will be used for each cell type-specific term. |

Value

a character vector, strings can be concatenated to OBO

Note

ldfToTerms is not sufficiently general to produce terms for any reasonably populated long data frame/propmap combination, but it is a working example for the cyclic set context.

Examples

```
# a set of cell types -- names are cell type token, values are genes expressed in a
# cyclic set -- each cell type expresses exactly one gene in the set and fails to
# express all the other genes in the set. See Figs 3 and 4 of Bakken et al [PMID 29322913].
sigels = c("CL:X01"="GRIK3", "CL:X02"="NTNG1", "CL:X03"="BAGE2",
           "CL:X04"="MC4R", "CL:X05"="PAX6", "CL:X06"="TSPAN12", "CL:X07"="hSHISA8",
           "CL:X08"="SNCG", "CL:X09"="ARHGEF28", "CL:X10"="EGF")
# create the associated long data frame
ldf = cyclicSigset(sigels)
# describe the abbreviations
pmap = c("hasExp"="has_expression_of", lacksExp="lacks_expression_of")

# now define the prolog for each cell type
makeIntnProlog = function(id, ...) {
# make type-specific prologs as key-value pairs
  c(
    sprintf("id: %s", id),
    sprintf("name: %s-expressing cortical layer 1 interneuron, human", ...),
    sprintf("def: '%s-expressing cortical layer 1 interneuron, human described via RNA-seq observations' [PMID 29322913]", ...),
    "is_a: CL:0000099 ! interneuron",
    "intersection_of: CL:0000099 ! interneuron")
}
tms = ldfToTerms(ldf, pmap, sigels, makeIntnProlog)
cat(tms[[1]], sep="\n")
```

liberalMap

Produce a data.frame with a set of naive terms mapped to all matching ontology ids and their formal terms

Description

Produce a data.frame with a set of naive terms mapped to all matching ontology ids and their formal terms

Usage

```
liberalMap(terms, onto, useAgrep = FALSE, ...)
```

Arguments

| | |
|----------|---|
| terms | character() vector, can use grep-compatible regular expressions |
| onto | an instance of ontologyIndex::ontology_index |
| useAgrep | logical(1) if TRUE, agrep will be used |
| ... | passed to agrep if used |

Value

a data.frame

Examples

```
cands = c("astrocyte$", "oligodendrocyte", "oligodendrocyte precursor",
          "neoplastic", "^neuron$", "^vascular", "badterm")
#co = ontoProc::getCellOnto()
co = getOnto("cellOnto", year_added="2023")
liberalMap(cands, co)
```

```
make_graphNEL_from_ontology_plot
```

obtain graphNEL from ontology_plot instance of ontologyPlot

Description

obtain graphNEL from ontology_plot instance of ontologyPlot

Usage

```
make_graphNEL_from_ontology_plot(x)
```

Arguments

x instance of S3 class ontology_plot

Value

instance of S4 graphNEL class

Examples

```
requireNamespace("Rgraphviz")
requireNamespace("graph")
c1 = getOnto("cellOnto")
c13k = c("CL:0000492", "CL:0001054", "CL:0000236", "CL:0000625",
        "CL:0000576", "CL:0000623", "CL:0000451", "CL:0000556")
p3k = ontologyPlot::onto_plot(c1, c13k)
gnel = make_graphNEL_from_ontology_plot(p3k)
gnel = improveNodes(gnel, c1)
```

```
graph::graph.par(list(nodes=list(shape="plaintext", cex=.8)))
gnet = Rgraphviz::layoutGraph(gnet)
Rgraphviz::renderGraph(gnet)
```

makeSelectInput *generate a selectInput control for an ontologyIndex slice*

Description

generate a selectInput control for an ontologyIndex slice

Usage

```
makeSelectInput(
  onto,
  term,
  type = "siblings",
  inputId,
  label,
  multiple = TRUE,
  ...
)
```

Arguments

| | |
|----------|---|
| onto | ontologyIndex instance |
| term | character(1) term used as basis for term list option set in the control |
| type | character(1) 'siblings' or 'children', relationship to 'term' that the options will satisfy |
| inputId | character(1) for use in server |
| label | character(1) for labeling in ui |
| multiple | logical(1) passed to selectInput |
| ... | additional parameters passed to selectInput |

Value

a [selectInput](#) control

Examples

```
makeSelectInput
```

| | |
|-----------|---|
| map2prose | <i>use prose terminology with output of connect_classes</i> |
|-----------|---|

Description

use prose terminology with output of connect_classes

Usage

```
map2prose(x, cl)
```

Arguments

| | |
|----|---------------------------------------|
| x | a component of connect_classes output |
| cl | an ontologyIndex ontology instance |

Value

a decorated list

| | |
|-------------|--|
| mapOneNaive | <i>use grep or agrep to find a match for a naive token into ontology</i> |
|-------------|--|

Description

use grep or agrep to find a match for a naive token into ontology

Usage

```
mapOneNaive(naive, onto, useAgrep = FALSE, ...)
```

Arguments

| | |
|----------|--|
| naive | character(1) |
| onto | an instance of ontologyIndex::ontology_index |
| useAgrep | logical(1) if TRUE, agrep will be used |
| ... | passed to agrep if used |

Value

if a match is found, the result of grep/agrep with value=TRUE is returned; otherwise a named NA_character_ is returned

named vector, names are ontology identifiers, values are matched strings

Examples

```
#co = ontoProc::getCellOnto()
co = getOnto("cellOnto", year_added="2023")
mapOneNaive("astrocyte", co)
```

| | |
|------------|---|
| minicorpus | <i>minicorpus: a vector of annotation strings found in 'study title' of SRA metadata.</i> |
|------------|---|

Description

minicorpus: a vector of annotation strings found in 'study title' of SRA metadata.

Usage

```
minicorpus
```

Format

character vector

Note

arbitrarily chosen from titles of RNA-seq studies for taxon 9606

Source

NCBI SRA

Examples

```
data(minicorpus)
head(minicorpus)
```

| | |
|--------------|--|
| nomenCheckup | <i>repair nomenclature mismatches (to curated term set) in a vector of terms</i> |
|--------------|--|

Description

repair nomenclature mismatches (to curated term set) in a vector of terms

Usage

```
nomenCheckup(cand, namedOffic, n = 1, tagcolname = "tag", ...)
```

Arguments

| | |
|------------|---|
| cand | character vector of candidate terms |
| namedOffic | named character vector of curated terms, the names are regarded as tags, intended to be identifiers in curated ontologies |
| n | numeric(1) number of nearest neighbors to return |
| tagcolname | character(1) prefix used to name columns for tags in output |
| ... | passed to <code>adist</code> |

Value

a data.frame instance with 2n+1 columns (column 1 is candidate, remaining n pairs of columns are (term, tag) for n nearest neighbors as measured by `adist`).

Examples

```

candidates = c("JHH7", "HUT102", "HS739T", "NCIH716")
# the candidates are cell line names returned in the text dump from
# https://portals.broadinstitute.org/ccle/page?gene=AHR
# note that one must travel to the third nearest neighbor
# to find the match (and tag) for Hs 739.T
# in this example, we compare to cell line names in Cell Line Ontology
nomenCheckup(candidates, cleanCLNames(), n=3, tagcolname="clo")

```

onto_plot2

high-level use of graph/Rgraphviz for rendering ontology relations

Description

high-level use of graph/Rgraphviz for rendering ontology relations

Usage

```
onto_plot2(ont, terms2use, cex = 0.8, ...)
```

Arguments

| | |
|-----------|---|
| ont | instance of ontology from ontologyIndex |
| terms2use | character vector |
| cex | numeric(1) defaults to .8, supplied to Rgraphviz::graph.par |
| ... | passed to onto_plot of ontologyPlot |

Value

graphNEL instance (invisibly)

Examples

```
c1 = getOnto("cellOnto")
c13k = c("CL:0000492", "CL:0001054", "CL:0000236", "CL:0000625",
        "CL:0000576", "CL:0000623", "CL:0000451", "CL:0000556")
onto_plot2(c1, c13k)
```

onto_roots *list parentless nodes in ontology_index instance*

Description

list parentless nodes in ontology_index instance

Usage

```
onto_roots(x)
```

Arguments

x an ontology_index instance

Value

a report (produced by cat()) of root ids and associated names

Examples

```
onto_roots
```

ontoDiff *Display Version Differences*

Description

Highlights in green the terms that are present in the new ontology but not the old one

Usage

```
ontoDiff(newonto, oldonto, terms2use, cex = 0.8, ...)
```

Arguments

newonto the newest version of the ontology
 oldonto the old version of the ontology
 terms2use terms of interest
 cex numeric(1) defaults to .8, supplied to Rgraphviz::graph.par
 ... passed to onto_plot of ontologyPlot

Value

onto_plot2 style plot with version differences highlighted

Note

Credit to ontoPlot for the use of some of its functions.

Examples

```
c1 = getOnto("diseaseOnto")
c12 = getOnto(ontoname = "diseaseOnto", year_added = "2021")
c13k = c("DOID:0040064", "DOID:0040076", "DOID:0081127", "DOID:0081126", "DOID:0081131", "DOID:0060034")
ontoDiff(c1,c12,c13k)
```

owl2cache

cache an owl file accessible via URL

Description

cache an owl file accessible via URL

Usage

```
owl2cache(cache = BiocFileCache::BiocFileCache(), url)
```

Arguments

| | |
|-------|--------------------------------------|
| cache | BiocFileCache instance or equivalent |
| url | character(1) |

Note

This function will check for presence of url in cache using bfcquery; if a hit is found, returns the rpath associated with the last matching record. etags can be available for use with bfcneedsupdate.

Examples

```
ca = BiocFileCache::BiocFileCache()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  hppa = owl2cache(ca,
    url="http://purl.obolibrary.org/obo/hp/releases/2023-10-09/hp-base.owl")
  setup_entities(hppa)
}
```

packDesc2019 *packDesc2019: overview of ontoProc resources*

Description

packDesc2019: overview of ontoProc resources

Usage

packDesc2019

Format

data.frame instance

Note

Brief survey of functions available to load serialized ontology_index instances imported from OBO.

Examples

```
data(packDesc2019)
head(packDesc2019)
```

packDesc2021 *packDesc2021: overview of ontoProc resources*

Description

packDesc2021: overview of ontoProc resources

Usage

packDesc2021

Format

data.frame instance

Note

Brief survey of functions available to load serialized ontology_index instances imported from OBO. Focus is on versions added in 2021.

Examples

```
data(packDesc2021)
head(packDesc2021)
```

`packDesc2022`*packDesc2022: overview of ontoProc resources*

Description

`packDesc2022`: overview of ontoProc resources

Usage

```
packDesc2022
```

Format

data.frame instance

Note

Brief survey of functions available to load serialized ontology_index instances imported from OBO. Focus is on versions added in 2022.

Examples

```
data(packDesc2022)
head(packDesc2022)
```

`packDesc2023`*packDesc2023: overview of ontoProc resources*

Description

`packDesc2023`: overview of ontoProc resources

Usage

```
packDesc2023
```

Format

data.frame instance

Note

Brief survey of functions available to load serialized ontology_index instances imported from OBO. Focus is on versions added in 2023. Several manual interventions were needed – cellosaurus was too large to use the script in inst/scripts/desc.R, and a number of ontologies do not have 2023 versions.

Examples

```
data(packDesc2023)
head(packDesc2023)
```

| | |
|---------|----------------------|
| parents | <i>retrieve is_a</i> |
|---------|----------------------|

Description

retrieve is_a

Usage

```
parents(oe)
```

Arguments

oe owlents instance

Value

list of vectors of tags of parents

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  orde
  parents(orde[1000:1001])
  labels(orde[1000:1001])
}
```

| | |
|--------------|--|
| plot.owlents | <i>visualize ontology selection via onto_plot2, based on owlents</i> |
|--------------|--|

Description

visualize ontology selection via onto_plot2, based on owlents

Usage

```
plot.owlents(x, y, ..., dropThing = TRUE)
```

Arguments

| | |
|-----------|---|
| x | owlents instance |
| y | character() vector of entries in x\$clnames |
| ... | passed to onto_plot2 |
| dropThing | logical(1) defaults to TRUE; if "Thing" is present in terms to display, it is removed |

Examples

```

c13k = c("CL:0000492", "CL:0001054", "CL:0000236",
        "CL:0000625", "CL:0000576",
        "CL:0000623", "CL:0000451", "CL:0000556")
c13k = gsub(":", "_", c13k)
clont_path = owl2cache(url="http://purl.obolibrary.org/obo/cl.owl")
tmp = readLines(clont_path)
# deal with ambiguity not accommodated by owlready2
bad = grep("STATO_0000416", tmp)[1:2] # see https://github.com/obophenotype/cell-ontology/issues/3237
tmp = tmp[-bad]
bad = grep("STATO_0000663", tmp)[1:2] # see https://github.com/obophenotype/cell-ontology/issues/3237
tmp = tmp[-bad]
tf = tempfile()
writeLines(tmp, tf)
cle = setup_entities2(tf)
ntag = gsub(":", "_", c13k)
onto_plot2(cle, ntag)

```

print.owlents *short printer*

Description

short printer

Usage

```

## S3 method for class 'owlents'
print(x, ...)

```

Arguments

| | |
|-----|------------------|
| x | owlents instance |
| ... | not used |

| | |
|--------|---|
| PROSYM | <i>PROSYM: HGNC symbol synonyms for PR (protein ontology) entries identified in Cell Ontology</i> |
|--------|---|

Description

PROSYM: HGNC symbol synonyms for PR (protein ontology) entries identified in Cell Ontology

Usage

PROSYM

Format

data.frame instance

Note

This is a snapshot of the synonyms component of an `extract_tags='everything'` import of PR. The `'EXACT.*PRO-short.*:DNx'` pattern is used to retrieve HGNC symbols. See `?getPROnto` for more provenance information.

Source

OBO Foundry

Examples

```
data(PROSYM)
head(PROSYM)
```

| | |
|-----------|---|
| quickOnto | <i>Probe the cache for entries found by bfcquery using the given query.</i> |
|-----------|---|

Description

Probe the cache for entries found by bfcquery using the given query.

Usage

```
quickOnto(query, cache = BiocFileCache::BiocFileCache(), qans.only = FALSE)
```

Arguments

| | |
|-----------|---|
| query | character(1), will be used by <code>BiocFileCache::bfcquery</code> |
| cache | instance of class(<code>BiocFileCache::BiocFileCache()</code>) |
| qans.only | logical, defaulting to FALSE, if TRUE, just return the bfcquery result. |

Note

Take only the last entry found if there are multiple hits. Use 'setup_entities2' to transform owl to ontologyIndex and cache the result if this is absent for the owl identified by query.

Examples

```
aeo = quickOnto("aeo.owl")
str(aeo)
```

recognizedPredicates *enumerate ontological relationships used in ontoProc utilities*

Description

enumerate ontological relationships used in ontoProc utilities

Usage

```
recognizedPredicates()
```

Value

character vector, names of elements are abbreviated tokens that may be used in code

Examples

```
head(recognizedPredicates())
```

search_labels *use owlready2 ontology search facility on term labels*

Description

use owlready2 ontology search facility on term labels

Usage

```
search_labels(ontopath, regexp, case_sensitive = TRUE)
```

Arguments

ontopath character(1) path to owl file
 regexp character(1) simple regular expression
 case_sensitive logical(1) should case be respected in search?

Value

A named list: term labels are elements, tags are names of elements. Will return NULL if nothing is found.

Examples

```
pa = get_ordo_owl_path()
ol = search_labels(pa, "*Immunog*")
orde = setup_entities2(pa)
onto_plot2(orde, names(ol))
```

| | |
|-----------|---|
| secLevGen | <i>simple generation of children of 'choices' given as terms, returned as TermSet</i> |
|-----------|---|

Description

simple generation of children of 'choices' given as terms, returned as TermSet

Usage

```
secLevGen(choices, ont)
```

Arguments

| | |
|---------|--|
| choices | vector of terms |
| ont | instance of ontology_index (S3) from ontologyIndex package |

Value

TermSet instance

Examples

```
efoOnto = getOnto("efoOnto")
secLevGen("disease", efoOnto)
```

| | |
|---------------|---|
| selectFromMap | <i>select a set of elements from a term 'map' and return a contribution to a data.frame</i> |
|---------------|---|

Description

select a set of elements from a term 'map' and return a contribution to a data.frame

Usage

```
selectFromMap(namedvec, index)
```

Arguments

| | |
|----------|--|
| namedvec | named character vector, as returned from mapOneNaive |
| index | numeric() or integer(), typically of length one |

Value

a data.frame; if index does not inherit from numeric, a data.frame of one row with columns 'ontoid' and 'term' populated with NA_character_ is returned, otherwise a similarly named data.frame is returned with contents from the selected elements of namedvec

Examples

```
#co = ontoProc::getCellOnto()
co = getOnto("cellOnto", year_added="2023")
mast = mapOneNaive("astrocyte", co)
selectFromMap(mast, 1)
```

| | |
|----------------|--|
| setup_entities | <i>construct owlents instance from an owl file</i> |
|----------------|--|

Description

construct owlents instance from an owl file

Usage

```
setup_entities(owlfn)
```

Arguments

| | |
|-------|---|
| owlfn | character(1) path to valid owl ontology |
|-------|---|

Value

instance of owlents, which is a list with cnames (a vector of term names in form '[namespace]_[tag]'), allents (a list with python references to owlready2 entities, that can be operated on using owlready2.EntityClass methods), owlfn (filename), iri (IRI), call (record of call producing the entity.)

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  orde
  ancestors(orde[1000:1001])
  labels(orde[1000:1001])
}
```

| | |
|-----------------|---|
| setup_entities2 | <i>preparing for a small number of entry points to owlready2 mediated by basilisk, this setup function will ingest OWL, enumerate classes and their names, and produce the 'parents' list, which can then be used with ontology_index to produce a functional ontology representation</i> |
|-----------------|---|

Description

preparing for a small number of entry points to owlready2 mediated by basilisk, this setup function will ingest OWL, enumerate classes and their names, and produce the 'parents' list, which can then be used with ontology_index to produce a functional ontology representation

Usage

```
setup_entities2(owlfn, cache_object = TRUE)
```

Arguments

owlfn character(1) path to OWL file
 cache_object logical(1) if TRUE, cache the 'ontology_index' instance in BiocFileCache::BiocFileCache()

Note

Production of an 'ontology_index' instance will often throw a warning when "Thing" is part of the ontology. suppressWarnings has been used in the code to suppress this. This may be too aggressive an approach.

Examples

```
pa = get_ordo_owl_path()
orde = setup_entities2(pa)
orde
```

| | |
|-----------|---|
| seur3kTab | <i>tabulate the basic outcome of PBMC 3K tutorial of Seurat</i> |
|-----------|---|

Description

tabulate the basic outcome of PBMC 3K tutorial of Seurat

Usage

```
seur3kTab()
```

Value

a data.frame

Examples

```
seur3kTab()
```

| | |
|--------------|---|
| siblings_TAG | <i>generate a TermSet with siblings of a given term, excluding that term by default</i> |
|--------------|---|

Description

generate a TermSet with siblings of a given term, excluding that term by default

acquire the label of an ontology subject tag

acquire the labels of children of an ontology subject tag

Usage

```
siblings_TAG(Tagstring = "EFO:1001209", ontology, justSibs = TRUE)
```

```
label_TAG(Tagstring = "EFO:0000311", ontology)
```

```
children_TAG(Tagstring = "EFO:1001209", ontology)
```

Arguments

Tagstring a character(1) that identifies a term

ontology instance of ontology_index (S3) from ontologyIndex

justSibs character(1)

Value

TermSet instance
character(1)
TermSet instance

Note

for label_TAG, Tagstring may be a vector

Examples

```
efoOnto = getOnto("efoOnto")
siblings_TAG( "EF0:1001209", efoOnto )
efoOnto = getOnto("efoOnto")
label_TAG( "EF0:0000311", efoOnto )
efoOnto = getOnto("efoOnto")
children_TAG( ontology = efoOnto )
```

stopWords

stopWords: vector of stop words from xpo6.com

Description

stopWords: vector of stop words from xpo6.com

Usage

```
stopWords
```

Format

character vector

Note

"Stop words" are english words that are assumed to contribute limited semantic value in the analysis of free text.

Source

<http://xpo6.com/list-of-english-stop-words/>

Examples

```
data(stopWords)
head(stopWords)
```

| | |
|------------|-----------------------------------|
| subclasses | <i>retrieve subclass entities</i> |
|------------|-----------------------------------|

Description

retrieve subclass entities

Usage

```
subclasses(oe)
```

Arguments

oe owlents instance

Examples

```
pa = get_ordo_owl_path()
o2 = try(reticulate::import("owlready2"), silent=TRUE)
if (!inherits(o2, "try-error")) {
  orde = setup_entities(pa)
  orde
  sc <- subclasses(orde[1:5])
  labels(orde[3])
  o3 = reticulate::iterate(sc[[3]])
  print(length(o3))
  o3[[2]]
  labels(orde["Orphanet_100011"])
}
```

| | |
|--------------------|--|
| subset_descendants | <i>subset a SummarizedExperiment to which ontology tags have been bound using 'bind_formal_tags', obtaining the 'descendants' of the class of interest</i> |
|--------------------|--|

Description

subset a SummarizedExperiment to which ontology tags have been bound using 'bind_formal_tags', obtaining the 'descendants' of the class of interest

Usage

```
subset_descendants(
  se,
  onto,
  class_name,
  class_tag,
  formal_cd_name = "label.ont"
)
```

Arguments

| | |
|----------------|--|
| se | SummarizedExperiment instance |
| onto | representation of an ontology using representation from ontologyIndex package |
| class_name | character(1) if 'class_tag' is missing, this will be grepped in onto[["name"]] to find class and its descendants |
| class_tag | character(1) used if given to identify "ontological descendants" of this term in se |
| formal_cd_name | character(1) tells name used for ontology tag column in 'colData(se)' |

Value

instance of SummarizedExperiment

| | |
|---------------|--|
| sym2Cell10nto | <i>use Cell Ontology and Protein Ontology to identify cell-type defining conditions in which a given gene is named</i> |
|---------------|--|

Description

use Cell Ontology and Protein Ontology to identify cell-type defining conditions in which a given gene is named

Usage

```
sym2Cell10nto(sym, cl, pr)
```

Arguments

| | |
|-----|--|
| sym | gene symbol, must be used in protein ontology as a PRO:DNx exact match token |
| cl | result of getOnto("cell10nto") |
| pr | result of getOnto("PROnto") |

Value

DataFrame if any hits are found. A field 'cond' abbreviates the identified conditions: (has/lacks)PMP (plasma membrane part) (hi/lo)PMAmt (plasma membrane amount), (has/lacks)Part.

Note

Currently just checks for *plasma_membrane_part, *plasma_membrane_amount, and *Part conditions.

Examples

```
if (!exists("cl")) cl = getOnto("cell10nto")
if (!exists("pr")) pr = getOnto("PROnto")
sym2Cell10nto("ITGAM", cl, pr)
sym2Cell10nto("FOXP3", cl, pr)
```

| | |
|---------------|---|
| TermSet-class | <i>manage ontological data with tags and a DataFrame instance</i> |
|---------------|---|

Description

manage ontological data with tags and a DataFrame instance
abbreviated display for TermSet instances

Usage

```
## S4 method for signature 'TermSet'  
show(object)
```

Arguments

object instance of TermSet class

Value

instance of TermSet

Examples

```
efo0nto = get0nto("efo0nto")  
defsibs = siblings_TAG("EFO:1001209", efo0nto)  
class(defsibs)  
defsibs
```

| | |
|--------|--|
| url_ok | <i>check that a URL can get a 200 for a HEAD request</i> |
|--------|--|

Description

check that a URL can get a 200 for a HEAD request

Usage

```
url_ok(url)
```

Arguments

url character(1)

Value

logical(1)

valid_ontonames *give a vector of valid 'names' of ontoProc ontologies*

Description

give a vector of valid 'names' of ontoProc ontologies

Usage

```
valid_ontonames()
```

Examples

```
head(valid_ontonames())
```

Index

* datasets

- allGOterms, 4
 - humrna, 23
 - minicorpus, 31
 - packDesc2019, 35
 - packDesc2021, 35
 - packDesc2022, 36
 - packDesc2023, 36
 - PROSYM, 39
 - stopWords, 45
- [.owlents, 3
- adist, 32
- agrep, 9
- allGOterms, 4
- ancestors, 5
- ancestors_names, 5
- available_ontos, 6
- bind_formal_tags, 6
- bioregistry_ols_resources, 7
- browse_ontos, 8
- c, TermSet-method, 8
- cellTypeToGenes (cellTypeToGO), 9
- cellTypeToGO, 9
- children_names, 10
- children_TAG (siblings_TAG), 44
- cleanCLNames, 10
- CLfeats, 11
- common_classes, 12
- connect_classes, 12
- ctmarks, 13
- cyclicSigset, 14
- DataFrame, 17
- demoApp, 15
- dropStop, 15
- fastGrep, 16
- findCommonAncestors, 17
- formalize, 18
- get_classes, 19
- get_ordo_owl_path, 20
- getCellosaurusOnto (getChebiLite), 20
- getChebiLite, 20
- getChebiOnto (getChebiLite), 20
- getDiseaseOnto (getChebiLite), 20
- getGeneOnto (getChebiLite), 20
- getHCAOnto (getChebiLite), 20
- getLeavesFromTerm, 21
- getMondoOnto (getChebiLite), 20
- getOncotreeOnto (getChebiLite), 20
- getOnto, 22
- getPATOnto (getChebiLite), 20
- getPROnto (getChebiLite), 20
- getSIOnto (getChebiLite), 20
- getUBERON_NE (getChebiLite), 20
- graph, 17
- graph2paths, 22
- humrna, 23
- improveNodes, 24
- jowl2classgraph, 24
- jowl2classgraph_nio, 25
- label_TAG (siblings_TAG), 44
- labels.owlents, 25
- ldfToTerms, 26
- liberalMap, 27
- List, 17
- make_graphNEL_from_ontology_plot, 28
- makeSelectInput, 29
- map2prose, 30
- mapOneNaive, 30, 42
- minicorpus, 31
- nomenCheckup, 31

onto_plot2, 32
onto_roots, 33
ontoDiff, 33
owl2cache, 34

packDesc2019, 35
packDesc2021, 35
packDesc2022, 36
packDesc2023, 36
parents, 37
plot.owlents, 37
print.owlents, 38
PROSYM, 39

quickOnto, 39

recognizedPredicates, 40

search_labels, 40
secLevGen, 41
selectFromMap, 42
selectInput, 29
setup_entities, 42
setup_entities2, 43
seur3kTab, 44
show (TermSet-class), 48
show, TermSet-method (TermSet-class), 48
siblings_TAG, 44
stopWords, 45
subclasses, 46
subset_descendants, 46
sym2CellOnto, 47

TermSet-class, 48
tolower, 15

url_ok, 48

valid_ontonames, 49